

What Is Claimed Is:

1. An aqueous emulsion composition comprising;
a high-solid-content emulsion compound which comprises;

(A) 100 parts by weight (solid basis) of at least
one latex or emulsion selected from the group
consisting of styrene-butadiene copolymer
latices, acrylic resin emulsions, ethylene-
vinyl acetate copolymer emulsions,
acrylonitrile-butadiene copolymer latices,
urethane resin emulsions, and natural rubber
latices,

(B) 0.3 to 2 parts by weight of a dispersing agent,

(C) 0.5 to 5 parts by weight of a crosslinking agent,

(D) 0.1 to 4 parts by weight of an anti-foaming agent,
and

(E) 100 to 600 parts by weight of at least one
powdered filler selected from the group
consisting of calcium carbonate, aluminum
hydroxide, silica sand, and barium sulfate; and

(F) 0.5 to 30 parts by weight of a polyisocyanate compound
having reactive isocyanate group, wherein the polyisocyanate
compound is added to the high-solid-content emulsion compound.

2. A method of backing a carpet, comprising the steps of
applying said aqueous emulsion composition according to claim

1 to the back of a carpet, and thermally curing and then drying

the emulsion composition applied.

3. A method of backing a carpet, comprising the steps of applying said aqueous emulsion composition according to claim 1 to the back of a carpet, laminating a fabric to the composition-applied surface of the carpet, and thermally curing and then drying the emulsion composition applied.

4. A carpet backed by the method according to claim 2.

5. A carpet backed by the method according to claim 3.